according to Regulation (EC) No. 1907/2006

Hardener EPH 294

Print date: 16.05.2011 Product code: 103105-2010 Page 1 of 8

1. Identification of the substance/mixture and of the company/undertaking

Identification of the substance or mixture

Hardener EPH 294

Use of the substance/mixture

epoxy resin hardener

Company/undertaking identification

Company name: R&G Faserverbundwerkstoffe GmbH

Composite Technology

Street: Im Meißel 7 - 13
Place: D-71111 Waldenbuch

Post-office box: 1145

D-71107 Waldenbuch

Telephone: +49-7157-530460 Telefax: +49-7157-530470

e-mail: info@r-g.de
Internet: www.r-g.de
Responsible Department: Management

Emergency telephone: poison information centre

2. Hazards identification

Classification

Indications of danger: Corrosive

R-phrases:

Harmful in contact with skin. Harmful if swallowed. Causes burns.

May cause sensitization by skin contact.

Harmful to aquatic organisms.

May cause long-term adverse effects in the aquatic environment.

GHS: Hazard categories:

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1 Respiratory/skin sensitization: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements: Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

3. Composition/information on ingredients

Chemical characterization (Mixture)

epoxy resin hardener

according to Regulation (EC) No. 1907/2006

Hardener EPH 294

Print date: 16.05.2011 Product code: 103105-2010 Page 2 of 8

Hazardous components

EC No.	CAS No.	Chemical name	Quantity
		Classification	
		GHS classification	
		Alkyletheramine	> 50%
		C R34	
220-666-8	2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	25-50%
		Xn, C R21/22-34-43-52-53	
		Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, Aquatic Chronic 3; H312 H302 H314 H317 H412	

Full text of R- and H-phrases: see section 16.

4. First aid measures

General information

Change contaminated clothing. Take the injured person out of the danger area and lay him/her down.

After inhalation

Provide fresh air. Consult physician. If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

After contact with skin, wash immediately with soap and plenty of water. Cover wound with sterile dressing.

After contact with eyes

After contact with eye rinse immediately with lot of water at least 5 minutes with open eyelid. Subsequently consult an opthalmologist.

After ingestion

Rinse mouth immediately and drink large quantities of water. Immediately get medical attention.

5. Fire-fighting measures

Suitable extinguishing media

Carbon dioxide (CO2).

Extinguishing powder.

Water fog.

Fight major fires with a water spray jet or alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

High power water jet.

Special exposure hazards arising from substance or mixture itself, combustion products, resulting gases

In case of fire may form:

Nitrogen oxides (NOx).

Carbon monoxide.

Ammonia.

Special protective equipment for fire-fighters

Wear a protective full body suit.

Wear breathing apparatus with own air supply.

Additional information

Contaminated fire-fighting water must be collected separately. Contaminated fire-fighting water must not get into the sewerage network. Fire residue and contaminated firefighting water must be disposed of in accordance with government regulations.

according to Regulation (EC) No. 1907/2006

Hardener EPH 294

Print date: 16.05.2011 Product code: 103105-2010 Page 3 of 8

6. Accidental release measures

Personal precautions

Wear personal protection equipment. Keep unprotected persons at a safe distance.

Environmental precautions

Do not empty into drains or the aquatic environment. Do not allow to enter the soil or subsoil. Do not allow to enter groundwater.

Methods for cleaning up/taking up

Provide adequate ventilation. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid-or universal binding agents). Dispose of contaminated material as § 13 waste.

7. Handling and storage

Handling

Advice on safe handling

Provide adequate ventilation/vapour extraction at the workplace.

Advice on protection against fire and explosion

No special measures are necessary.

Storage

Requirements for storage rooms and vessels

Ventilate adequately storage and work rooms. Employ reliable measures to prevent the product from entering the soil.

8

Further information on storage conditions

Keep in well sealed receptacles at a cool, dry location.

Storageclass (D):

8. Exposure controls/personal protection

Exposure limit values

Exposure controls

Protective and hygiene measures

Take off immediately all contaminated clothing Avoid contact with skin and eyes. "Wash hands when done working with material; at breaks, lunch, shift changes, etc." Do not breathe in gases/vapours/aerosols.

Respiratory protection

Not necessary when the room is well ventilated.

Hand protection

Wear protective gloves. (EN 374)

Material: NBR (Nitrile rubber). Butyl rubber.

Breakthrough time: See information supplied by the manufacturer.

Eye protection

Tightly sealed safety glasses. (EN 166)

Skin protection

Wear protective clothing. (EN 368/9)

according to Regulation (EC) No. 1907/2006

Hardener EPH 294

Print date: 16.05.2011 Product code: 103105-2010 Page 4 of 8

9. Physical and chemical properties

General information

Physical state: liquid
Colour: green
Odour: amine-like

Important health, safety and environmental information

Test method

Changes in the physical state

Boiling point: $> 240 \, ^{\circ}\text{C}$ DIN 53171 Flash point: $> 110 \, ^{\circ}\text{C}$ ISO 2719

Lower explosion limits: Upper explosion limits:

Density (at 20 °C): 0,933 - 0,935 g/cm³ DIN 53217

Water solubility: completely soluble

Viscosity / dynamic: 40 - 80 mPa·s ISO 9371

(at 25 °C)

Other information

Ignition temperature: > 200 °C DIN 51794

10. Stability and reactivity

Conditions to avoid

no decomposition when stored and handled properly

Materials to avoid

strong exothermal reaction with: acid.

Hazardous decomposition products

Gas / vapours, corrosive.

Ammonia.

11. Toxicological information

Specific effects in experiment on an animal

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine:

oral: 1.030 mg/kg (rat) LD50 dermal: 1.840 mg/kg (rabbit) LD50

Irritation and corrosivity

Caustic effect on eyes, skin, and mucous membranes.

Sensitizing effects

Contact may cause skin sensitisation.

Additional information on tests

When swallowed strong caustic effect on oral cavity and throat and risk of oesophagus and stomach perforation.

12. Ecological information

Further information

Do not let the product enter the groundwater, open water, or the sewerage system.

according to Regulation (EC) No. 1907/2006

Hardener EPH 294

Print date: 16.05.2011 Product code: 103105-2010 Page 5 of 8

13. Disposal considerations

Advice on disposal

Dispose of waste according to applicable local, state, and federal regulations. e.g. transfer to a suitable incineration plant Waste key numbers are assigned according to the European Waste Catalogue (EWC) depending on the sector and process type.

Contaminated packaging

Dispose of waste according to applicable local, state, and federal regulations.

14. Transport information

Land transport (ADR/RID)

UN number: 2735
ADR/RID class: 8
Classification code: C7

Warning plate

Hazard-no.: 80
Hazard label: 8



ADR/RID packing group: III
Limited quantity: LQ7
Tunnel restriction code: E

Description of the goods

POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Alkyletheramin)

Other applicable information (land transport)

Special provisions: 274

E0 : 1

Marine transport

UN number: 2735
IMDG code: 8
Marine pollutant: •
Hazard label: 8



IMDG packing group:

EmS: F-A, S-B Limited quantity: None

Description of the goods

POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Alkyletheramine)

Other applicable information (marine transport)

Special provisions: 274

E0

according to Regulation (EC) No. 1907/2006

Hardener EPH 294

Print date: 16.05.2011 Product code: 103105-2010 Page 6 of 8

Air transport

UN/ID number: 2735
ICAO/IATA-DGR: 8
Hazard label: 8



ICAO packing group:
Limited quantity Passenger:
-

IATA-packing instructions - Passenger: 807
IATA-max. quantity - Passenger: 0.5 L
IATA-packing instructions - Cargo: 809
IATA-max. quantity - Cargo: 2.5 L

Description of the goods

POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Alkyletheramine)

Other applicable information (air transport)

E0

Special provisions: A3

15. Regulatory information

Labelling

Danger symbols: C - Corrosive



C - Corrosive

Hazardous components which must be listed on the label

Isophorondiamin Alkyletheramin

R phrases

21	Harmful in contact with skin.
22	Harmful if swallowed.
34	Causes burns.
43	May cause sensitization by skin contact.
52	Harmful to aquatic organisms.

May cause long-term adverse effects in the aquatic environment.

S phrases

26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.	
36	Wear suitable protective clothing.	
37	Wear suitable gloves.	
20	Management of the second of th	

Wear eye/face protection.In case of accident or if yo

In case of accident or if you feel unwell, seek medical advice immediately (show the label where

possible).

This material and its container must be disposed of as hazardous waste.

Avoid release to the environment. Refer to special instructions / Safety data sheets.

according to Regulation (EC) No. 1907/2006

Hardener EPH 294

Print date: 16.05.2011 Product code: 103105-2010 Page 7 of 8

Additional advice on labelling

The product is classified and labelled under the EC Directives/hazardous substances laws (GefStoffV).

GHS labelling

Signal word: Danger

Pictograms: corrosion; exclamation mark





Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash ... thoroughly after handling.

P270 Do no eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P330 Rinse mouth.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P321 Specific treatment (see ... on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P352 Wash with plenty of soap and water.
P363 Wash contaminated clothing before reuse.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

P310 Immediately call a POISON CENTER or doctor/physician.

P321 Specific treatment (see ... on this label).

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

P405 Store locked up.

P501 Dispose of contents/container to

EU regulatory information

Additional information

EC-identification.

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

Additional information

APME document: "Epoxidharze und Härter (Toxikologie, Arbeitssicherheit, Umwelt)" ("Epoxy resins and hardeners (toxicology, work safety, environment)")

according to Regulation (EC) No. 1907/2006

Hardener EPH 294

Print date: 16.05.2011 Product code: 103105-2010 Page 8 of 8

16. Other information

Full text of R-phrases referred to under sections 2 and 3

21	Harmful in contact	with skin.

21/22 Harmful in contact with skin and if swallowed.

22 Harmful if swallowed.

34 Causes burns.

43 May cause sensitization by skin contact.

52 Harmful to aquatic organisms.

53 May cause long-term adverse effects in the aquatic environment.

Full text of H-Statements referred to under sections 2 and 3

H302	Harmful if swallowed.
H312	Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Further Information

All information, recommendations, and advice on the part of R&G Faserverbundwerkstoffe GmbH are published to the best of our knowledge and belief. They are noncommittal and contain neither explicit nor tacit assurance or warranty of particular properties. The values specified for properties are typical figures. Recommendations or advice serve to describe our products and possible applications in a general or exemplary, but not specifically individual manner. In the course of the constant technical advancement and improvement of our products there may be changes to the characteristic values, copy, and diagrams; no specific reference is made to any such change. Owing to our products' wide and highly diverse range of potential applications far beyond any of our attempts to analyse, the customer alone is responsible for examining our products' suitability for the respective processes and purposes and their respective processibility. All and any protective rights and the applicable laws, terms, and conditions must be observed by the buyer or user of our products at their own responsibility. Publication is not a licence and does not intend the violation of any patents.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)