

Diaphragm Pumps for Air, Gases and Vapours

INNOVATIVE
TECHNOLOGY
WORLDWIDE

KNF
NEUBERGER



Diaphragm Vacuum Pumps and Compressors

Technical features:

- 100% oil-free transfer
- Pure transfer, evacuation and compression
- Versions for slightly aggressive or corrosive gases and vapours
- Maintenance-free
- Environmentally friendly
- Gastight, leakage rate approx. 6×10^{-3} mbar x l/s, not tested in serial production.

Series N 035 A_.18 Pumps

Series N 035 diaphragm pumps are single-head, dry-running devices used in a wide range of laboratory applications. They transfer, compress and pump down without contamination. The pumps are available in various versions differing in the materials which contact the media.

Material in contact with the pumped media

Type/OrderNo.	Pump head	Diaphragm	Valves
N 035 AN.18	Aluminium	CR	Stainless steel
N 035 AT.18	Aluminium	PTFE-coated	Stainless steel

Choose the pump and the motor in accordance with the following example:

N 035 AN.18 with IP 44-Motor.

Versions for slightly aggressive gases and vapours

Technical data:

	N 035 AN.18 IP 20-Motor	N 035 AN.18 IP 44-Motor
Delivery (l/min) ¹⁾	30	30
Ultimate vacuum (mbar abs.)	100	100
Operating pressure (bar g)	4	4
Connectors for tube (mm)	ID 9	ID 9
Permissible gas and ambient temperature	+5...+40 °C	+5...+40 °C
Voltage/Frequencies	230V/50Hz	230V/50Hz
Motor protection	IP 20	IP 44
Power P ₁	220 W	230 W
Operating current	1 A	1.7 A
Weight	8.2 kg	8.5 kg
Dimensions		
LxHxW (mm)	265/254/143	280/255/198
With thermal switch		

Motors with other voltages and frequencies on request.

¹⁾ at atm. pressure

	N 035 AT.18 IP 20-Motor	N 035 AT.18 IP 44-Motor
Delivery (l/min) ¹⁾	27	27
Ultimate vacuum (mbar abs.)	100	100
Operating pressure (bar g)	4	4
Connectors for tube (mm)	ID 9	ID 9
Permissible gas and ambient temperature	+5...+40 °C	+5...+40 °C
Mains	230V/50Hz	230V/50Hz
Motor protection	IP 20	IP 44
Power P ₁	220 W	230 W
Operating current	1 A	1.7 A
Weight	8.2 kg	8.5 kg
Dimensions		
LxHxW (mm)	265/254/143	280/255/198
With thermal switch		

Motors with other voltages and frequencies on request.

¹⁾ at atm. pressure

Accessories

Description	Details	for Type	Order No.
Silencer/Filter	G 1/4		000352
Pressure relief valve	4 bar	N 035 AN.18	047601
Fine control valve with pressure gauge	pressure side	N 035 AN.18	000482
Fine control valve with vacuum gauge	suction side	N 035 AN.18	000354

KNF reserves the right to make changes.


KNF 1/2011 Produced in Germany

Diaphragm Pumps for Air, Gases and Vapours




Dimensions and performance characteristics

Pump down time for 20 l receiver



Performance characteristics



Dimensions (mm)

